## iPad Displays (freestanding)

Assembly Instructions



## Inserting iPad into enclosure









If using the iPad 2 or iPad 3 please insert the iPad into the silicon protective sleeve provided, to minimise movement within the enclosure.



Carefully place iPad into enclosure back section, ensuring that the home button is adjacent to the lock aperture.



Slide cover back into position and secure with lock.

## Assembling collar mount to iPad holder



Place acrylic collar over the bottom of the iPad holder arm. Ensure that the larger diameter aperture is adjacent to the threaded insert (as shown).



Remove disc from packaging, align the arrows on the disc and arm, and press together.






Secure assembly, using the allen key and black screw provided.

## iPad Displays (freestanding)



**WARNING** – large base plate is heavy (7.5kg). Position base plate over 8-way post and align 4 off fixing holes to threads of post (ensuring the countersunk holes are uppermost).





Assemble additional posts, if required, and then place aluminium plate onto top of post. Align the 4 holes of the plate to the threads of the post. If mounting iPad to centre of Podium top, please move to stage 5.



Position collar mount of iPad holder over aluminium plate. Align holes, insert 2 off fixing screws, and tighten to secure assembly. Move to stage 7.



Align Podium top to aluminium plate, in the same direction as the base plate. Insert and tighten 2 off fixing screws in diametrically opposite positions.



Place additional aluminium plate on Podium top, followed by the collar mount of the iPad holder. Align holes, insert remaining 2 off fixing screws, and tighten to secure assembly.

